



CSM340C

S-CSM340C

Surface Mount Schottky Barrier Rectifiers
Reverse Voltage 40V Forward Current 3.0A

1. FEATURES

- We declare that the material of product complies with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0.
- Low power loss, high efficiency.
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications.
- High temperature soldering guaranteed: 260°C/10 seconds.
- Weight: 0.26g



2. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
SM340C	SM340C	3000/Tape&Reel
S-SM340C	SM340C	3000/Tape&Reel

3. MAXIMUM RATINGS (Ta = 25°C)

Parameter	Symbol	Limits	Unit
Maximum repetitive peak reverse voltage	VRRM	40	V
Maximum RMS voltage	VRMS	28	V
Maximum DC blocking voltage	VDC	40	V
Maximum average forward rectified current at TC = 75°C	IF(AV)	3	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	80	A
Typical thermal resistance (Note 1)	RθJA	80	°C/W
	RθJC	20	
Operating junction and storage temperature range	TJ, TSTG	-50 ~+150	°C

4. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Maximum instantaneous forward voltage at 3.0A	VF	-	-	0.55	V
Maximum DC reverse current TA = 25°C at rated DC blocking voltage TJ = 125°C	IR	-	-	0.5	mA
		-	-	10	
Typical junction capacitance at 4.0V, 1MHz	CJ	-	150	-	pF

1. Mounted on 0.31 x 0.31" (8.0 x 8.0mm) copper pads to each terminal.

5. ELECTRICAL CHARACTERISTICS CURVES

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-repetitive Peak Forward Surge Current




Fig 3. - Typical Instantaneous Forward Characteristics




Fig 4. - Typical Reverse Characteristics








Fig 5. - Typical Junction Capacitance




6. OUTLINE AND DIMENSIONS

CSMC



CSMC			
DIM	MIN	TYP	MAX
A	2.25	2.45	2.65
A1	0.05	0.10	0.20
b	2.80	3.00	3.20
c	0.10	0.20	0.30
D	5.85	6.05	6.25
E	6.65	6.95	7.11
HE	7.70	8.00	8.30
L	0.76	1.20	1.52
All Dimensions in mm			

7. SOLDERING FOOTPRINT



CSMC	
DIM	(mm)
X	1.60
Y	3.30
C	6.60

DISCLAIMER

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.