

2.0x1.6 SMD Crystal

Part Number Guide

T-M-FF.FFFM-LC-FTFS-OT-ESR

T (Type型号): KC=2.0x1.6 SMD 4pads

M (Mode of Operation振荡模式): F=Fundamental

F (Frequency标称频率): Normal - 5 digitals of Frequency, e.g. 26.000M

Special - All digitals of Frequency, e.g. 28.63636M

LC (Load Capacitance负载电容): 20=20pf 00=series, etc


FT (Frequency Tolerance调整频差): 30=±30 ppm, etc

FS (Frequency Stability温度频差): 50=±50 ppm, etc

OT (Operating Temperature工作温度): 1060=-10°C to +60°C 4085=-40°C to +85°C, etc

ESR (Equivalent Series Resistance等效阻抗)

A (Automotive车载应用)



Electrical Specifications 电气参数

Item 项目	Spec 规格	Condition 条件
Frequency Range 频率范围	16MHz~60MHz	For further questions regarding specifications, please feel free to contact us. 对于超出标准的规格, 请联系我们
Operating Temperature 工作温度	-40~85°C, -55~125°C	
Drive Level 激励功率	100 μw max	It is recommended to use 1 μw~100 μw 推荐1 μw~100 μw
Load Capacitance 负载电容	5pF~∞	For further questions regarding specifications, please feel free to contact us. 对于超出标准的规格, 请联系我们
Frequency Tolerance 调整频差	±30ppm Standard (±10~±50ppm Available)	
Frequency Stability 温度频差	±30ppm@-40~85°C ±50ppm@-55~125°C	
Aging 老化率	±3ppm, F0<30MHz ±5ppm, F0≥30MHz	
Storage Temperature 储存温度	-55~125°C	
ESR 等效阻抗 (Ω)	16MHz≤F0<20MHz	
	20MHz≤F0<30MHz	100 Ω
	30MHz≤F0<60MHz	80 Ω

Mechanical Dimensions 外型尺寸

