

5x3.2 SMD Crystal

Part Number Guide

T-M-FF.FFFM-LC-FTFS-OT-ESR

T (Type型号): I=5×3.2 SMD 4pads

IB=5×3.2 SMD 2pads

M (Mode of Operation 振荡模式): F=Fundamental T=Third Overtone, etc

F (Frequency 标称频率): Normal - 5 digitals of Frequency, e.g. 8.0000M, 12.000M

Special - All digitals of Frequency, e.g. 13.225625M

LC (Load Capacitance 负载电容): 20=20pf 00=series, etc


FT (Frequency Tolerance 调整频差): 30=±30 ppm, etc

FS (Frequency Stability 温度频差): 50=±50 ppm, etc

OT (Operating Temperature 工作温度): 1060=-10°C to +60°C 4085=-40°C to +85°C, etc

ESR (Equivalent Series Resistance 等效阻抗)

A (Automotive 车载应用)



Electrical Specifications 电气参数

Item 项目	Spec 规格	Condition 条件	
Frequency Range 频率范围	8MHz~60MHz	For further questions regarding specifications, please feel free to contact us. 对于超出标准的规格, 请联系我们	
Operating Temperature 工作温度	-40~85°C, -55~125°C		
Drive Level 激励功率	100 μw max	It is recommended to use 1 μw~100 μw 推荐 1 μw~100 μw	
Load Capacitance 负载电容	5pF~∞	For further questions regarding specifications, please feel free to contact us. 对于超出标准的规格, 请联系我们	
Frequency Tolerance 调整频差	±30ppm Standard (±10~±50ppm Available)		
Frequency Stability 温度频差	±30ppm@-40~85°C ±50ppm@-55~125°C		
Aging 老化率	±3ppm, F0<30MHz ±5ppm, F0≥30MHz		
Storage Temperature 储存温度	-55~125°C	For further questions regarding specifications, please feel free to contact us. 对于超出标准的规格, 请联系我们	
ESR 等效阻抗 (Ω)	8MHz ≤ F0 < 10MHz		100 Ω
	10MHz ≤ F0 < 12MHz		80 Ω
	12MHz ≤ F0 < 16MHz		60 Ω
	16MHz ≤ F0 < 20MHz		50 Ω
	20MHz ≤ F0 < 24MHz		40 Ω
	24MHz ≤ F0 < 60MHz	30 Ω	

Mechanical Dimensions 外型尺寸

